

Modify Date : 06 / 25 / 2003

There is two models in this series.

1. P4MAC-MNB
2. P4MAC-MLB

Model Name	P4MAC-MNB	P4MAC-MLB
Form-Factor	micro ATX	
Dimension	244mm X 230 mm	
Processor	Intel PENTIUM 4 SOCKET 478	
FSB Clock	400/533MHz	
N/B Core Chipset	VIA P4M266A (CD) or (CE)	
S/B Core Chipset	VIA VT8235 (CD)	
BIOS	2Mb Flash ROM, Award BIOS support ACPI, PnP and DMI	
BIOS file name	P4MACMNB.B1x	P4MACMLB.B1x
System Memory	DDR DIMM x 2, support DDR200 and DDR266 (Max. 1GB)	
I/O chipset	Winbond W83697HF	
Hardware Monitoring	Yes	
Onboard Audio	AC'97 Codec 2 channel	
AC'97 Codec	VIA VT1612A	
Onboard VGA	On Chip ProSavage DDR	
Onboard LAN	None	VIA VT6103
PCI Slot	3	
CNR Slot	1	
AGP Slot	1 (2X/4X)	
USB Port	6 (ver:2.0), 2 ports on-board, 4 ports use header	
IDE	2 (support ATA 33/66/100/133)	
FDC	Yes	
PS/2 Keyboard	Yes	
PS/2 Mouse	Yes	
COM 1	Yes	
LPT	Yes	
Game and MIDI	Yes	
CD-IN connector	1	
Aux-IN connector	1	
FAN connector	2	
WOL connector	Yes	
Intel Type Front USB	Yes	
Intel Type Front AUDIO	Yes	
Hyper-Threading	Yes	